

客戶名稱 CUSTOMERS:			
日期 DATE:			
產品名稱 PRODUCT:	Fixed Carbon Film Resistors (CF Series) 碳素皮膜固定電阻器		
物料代號 PART NO.:	Customer	版本 REV.:	V10.12
	Queen Mao	CF□□□□-□□□-□□□□R□	

# 規格承認書 APPROVAL SHEET



客戶承認簽印 CUSTOMER APPROVED BY	核准 APPROVE	主管 CHIEF	承辦 RESPONSIBLE
APPROVED NO.:	ECN.:	/	/
MODEL:		/	/
CUSTOMER P/N:		/	/



昆 貿 電 子 股 份 有 限 公 司  
**QUEEN MAO ELECTRONIC CO., LTD.**

22178 新 北 市 汐 止 區 大 安 街 56 巷 35 號  
 No. 35, LANE 56, DA'AN STREET, XIZHI DISTRICT, NEW TAIPEI CITY 22178, TAIWAN (R.O.C.)

TEL: 886-2-8648-5566 FAX: 886-2-8648-0538

E-mail: [service@queenmao.com.tw](mailto:service@queenmao.com.tw)

URL: <http://www.queenmao.com.tw>



1. 一般事項 General

1.1 適用範圍 Scope

本承認書適用於[碳素皮膜固定電阻器]。  
This specification covers Fixed Carbon Film Resistors.

1.2 品質 Quality


本電阻器的製造係經高品質管理程序，並具有高信賴性的品質保證，且符合 RoHS 和無鹵要求。  
The resistor is manufactured by highly quality-controlled process and guaranteed high reliability, it meets RoHS & Halogen-Free requirement.

1.3 標準試驗狀態 Standard measuring conditions

溫度 20±2°C、濕度 65±5%。  
但在溫度 5~35°C、濕度 45~85%之情況下，仍可給予判定。  
Temperature 20±2°C, Humidity 65±5%.  
Being no doubt about the judgment, measurements can be made within the following Temperature 5~35°C, Humidity 45~85%.

1.4 形名 (例) Type designation (example)

依使用種類、額定電力、形狀、公稱電阻值、電阻值容許差而區別，其構造如下：  
The type designation shall be in the following form and as specified.



Examples

記號 Code	電阻值 Resistance value
0.12R	0.12Ω
100R	100Ω
1.2KR	1.2KΩ
10KR	10KΩ
12MR	12MΩ



1.5 額定電力 Rated power

額定電力係適應在周圍溫度 70°C 可以連續負載的最大電力，如表-1；但周圍溫度如超過 70°C 時之額定電力則依圖一的電力輕減曲線實施。

Rated power is maximum power which can be continuously loaded at specified ambient temperature 70°C, however when the ambient temperature exceeds 70°C, rated power should be determined from the derating curve of Fig.1.


表-1 Table-1

種類 Type	額定電力 Rated power	最高 使用電壓 Maximum working voltage	最高 過負荷電壓 Maximum overload voltage	最高 斷續電壓 Maximum pulse voltage	耐電壓 Dielectric withstanding voltage	電阻值範圍 Resistance range	使用溫度範圍 Operating temperature range
Normal size	CF1/8W(1/6W)	0.125W	250V	400V	500V	300V	2.2Ω ~ 2.2MΩ
	CF1/4W	0.25W	300V	600V	750V	500V	2.2Ω ~ 4.7MΩ
	CF1/2W	0.5W	350V	700V	1000V	700V	2.2Ω ~ 5.1MΩ
	CF1W	1W	500V	1000V	1500V	1000V	2.2Ω ~ 5.1MΩ
	CF2W	2W	750V	1500V	2000V	1000V	2.2Ω ~ 5.1MΩ
	CF3W	3W	750V	1500V	2000V	1000V	2.2Ω ~ 5.1MΩ
Small size	CF1/4WS	0.25W	250V	400V	500V	300V	2.2Ω ~ 2.2MΩ
	CF1/2WS	0.5W	300V	600V	750V	500V	2.2Ω ~ 4.7MΩ
	CF1WS	1W	350V	700V	1000V	700V	2.2Ω ~ 5.1MΩ
	CF2WS	2W	500V	1000V	1500V	1000V	2.2Ω ~ 5.1MΩ
	CF3WS	3W	750V	1500V	2000V	1000V	2.2Ω ~ 5.1MΩ

-55°C ~ 155°C

Note: 1. Special resistance range min. 0.1Ω, max. 10MΩ (±1%, min. 0.22Ω, max. 220KΩ), but character is not guaranteed.  
2. Please refer the material list in the item 2.2.

圖一 電力輕減曲線 Figure 1 Power derating curve





1.6 額定電壓 Rated voltage

額定電壓係指對應於額定電力的直流或交流（商用頻率之有效值）的電壓，由下式求得。但所求得之額定電壓超過表一所示之最高使用電壓時則以最高使用電壓為額定電壓。

The rated voltage shall be the D.C. or A.C. (R.M.S. at power frequency) voltage which corresponds the rated power and the value of which is calculated from the formula below. If the rated voltage exceeds the maximum voltage, the maximum voltage will apply.

$$E = \sqrt{P \cdot R}$$

Where E：額定電壓 Rated voltage (V)  
P：額定電力 Rated power (W)  
R：公稱電阻值 Norminal resistance ( $\Omega$ )

1.7 公稱電阻值 Nominal resistance values

公稱電阻值係按表-2 之數乘以  $10^n$  (n 為整數) 之數值，其單位為歐姆( $\Omega$ )。公稱電阻值之範圍則按表-1 所示。

The nominal resistance values shall be the numerical values given in Table-2 multiplied by  $10^n$  (n is an integer) in the unit of ohm( $\Omega$ ).

The minimum resistance and maximum resistance shall be as given in Table-1.

表-2 電阻值有效數字的標準 Table-2 Standard nominal resistance values

系列名 Name of series	標準公稱電阻值 (為有效數字，單位省略) Standard nominal resistance values (significant figures with the unit omitted)
E-6	1.0, 1.5, 2.2, 3.3, 4.7, 6.8
E-12	1.0, 1.2, 1.5, 1.8, 2.2, 2.7, 3.3, 3.9, 4.7, 5.6, 6.8, 8.2
E-24	1.0, 1.1, 1.2, 1.3, 1.5, 1.6, 1.8, 2.0, 2.2, 2.4, 2.7, 3.0, 3.3, 3.6, 3.9, 4.3, 4.7, 5.1, 5.6, 6.2, 6.8, 7.5, 8.2, 9.1
E-48	1.00, 1.05, 1.10, 1.15, 1.21, 1.27, 1.33, 1.40, 1.47, 1.54, 1.62, 1.69, 1.78, 1.87, 1.96, 2.05, 2.15, 2.26, 2.37, 2.49, 2.61, 2.74, 2.87, 3.01, 3.16, 3.32, 3.48, 3.65, 3.83, 4.02, 4.22, 4.42, 4.64, 4.87, 5.11, 5.36, 5.62, 5.90, 6.19, 6.49, 6.81, 7.15, 7.50, 7.87, 8.25, 8.66, 9.09, 9.53
E-96	1.00, 1.02, 1.05, 1.07, 1.10, 1.13, 1.15, 1.18, 1.21, 1.24, 1.27, 1.30, 1.33, 1.37, 1.40, 1.43, 1.47, 1.50, 1.54, 1.58, 1.62, 1.65, 1.69, 1.74, 1.78, 1.82, 1.87, 1.91, 1.96, 2.00, 2.05, 2.10, 2.15, 2.21, 2.26, 2.32, 2.37, 2.43, 2.49, 2.55, 2.61, 2.67, 2.74, 2.80, 2.87, 2.94, 3.01, 3.09, 3.16, 3.24, 3.32, 3.40, 3.48, 3.57, 3.65, 3.74, 3.83, 3.92, 4.02, 4.12, 4.22, 4.32, 4.42, 4.53, 4.64, 4.75, 4.87, 4.99, 5.11, 5.23, 5.36, 5.49, 5.62, 5.76, 5.90, 6.04, 6.19, 6.34, 6.49, 6.65, 6.81, 6.98, 7.15, 7.32, 7.50, 7.68, 7.87, 8.06, 8.25, 8.45, 8.66, 8.87, 9.09, 9.31, 9.53, 9.76



2. 構造 Construction

2.1 外形寸法 External dimensions


參照本任樣書的「5. 外形寸法」。

The dimensions shall be satisfied with 「5. External dimensions」.

2.2 構造圖 Structure diagram

CF 系列之碳素皮膜固定電阻器係按下表的材料而構成：

The construction of resistor (CF series) shall be as follows：



號碼 No.	構造名稱 Item	內容 Material
1	導線 Lead wire	焊錫或鍍錫的軟銅線。 Soldered or tinned annealed copper wire.
2	連接 Connection	導線對鐵帽須以電氣熔接。 The lead wire, which is plated with solder, shall be mounted to the caps by welding process.
3	端子 Terminal	鐵帽。 Tinned iron cap.
4	基體磁器 Ceramic core	使用高含鋁量的瓷器棒。 High alumina ceramic is used.
5	電阻體 Resistance element	電阻體的成份係使用碳素皮膜， 但電阻值低於 2.2Ω 以下時，係使用金屬皮膜。 The resistor element shall consist of carbon film, but use metal film when the resistance is less than 2.2Ω.
6	絕緣塗裝 Insulation coating	使用環氧樹脂塗料。 Epoxy resin is used.
7	表示 Indication	色碼。 Color code.



2.3 鐵帽端子 Terminal caps

鐵帽端子須確實地連接(電氣的及機械的)於電阻體上。

The caps shall be securely connected with the resistor element electrically and mechanically.

2.4 塗裝 Painting


2.4.1 本體必須依照仕様書之規定以絕緣塗料絕緣之。

Coating in accordance with specification insulates the body.

2.4.2 塗裝時 1/8W(1/4WS)的電阻其焊點和端子線可允許被塗料覆蓋的總長為  $C=3.4\text{mm}(\text{Max.})$ ，1/4W 以上(1/2WS 以上) 的電阻其焊點和端子線可允許被塗料覆蓋為  $t=1.0\text{mm}(\text{Max.})$ ，而端面、焊點和端子線可允許不被塗料覆蓋，端面部份被塗料覆蓋的限定值為  $1/2D$ 。

The 1/8W(1/4WS) resistors, welding point and Lead wire is permissible to be covered  $t=3.4\text{mm}(\text{Max.})$ , for over 1/4W(over 1/2WS) resistors, welding point and Lead wire is permissible to be covered  $t=1.0\text{mm}(\text{Max.})$ .

But welding point, terminal and lead wire, is permissible to be exposed without the outer coated cover. The extent should be within  $1/2$  of the arc angle.



2.5 外裝色澤 Resistor body color

表-3 Table-3

種類 Type	顏色 Color	種類 Type	顏色 Color
普通型 Normal Size	淺棕色 Light Brown	小型化 Small Size	深棕色 Dark Brown

2.6 表示 Indication

參照本仕様書的「4. 表示」。

The indication shall be satisfied with 「4. Indication」.



3. 特性 Characteristics

表-4 Table-4

項目 Item	規格值 Performance					試驗方法 (依據 JIS C 5202) Test methods (Conform to JIS C 5202)
溫度係數 Temperature coefficient	T. C. R. 種類 Type	±450 (PPM/°C)	-700 (PPM/°C)	-1000 (PPM/°C)	-1300 (PPM/°C)	5.2 項參照 Comply with 5.2  $\frac{R_1 - R_0}{R_0(T_1 - T_0)} \times 10^6 \text{ (PPM/°C)}$ R <sub>0</sub> : 室溫(T <sub>0</sub> )所測量之電阻值。 R <sub>1</sub> : 室溫+100°C(T <sub>1</sub> )後所測量之電阻值。 R <sub>0</sub> : Resistance value at room temp. (T <sub>0</sub> ). R <sub>1</sub> : Resistance value at room temp. plus 100°C (T <sub>1</sub> ).
	1/8W (1/6W) & 1/4WS	Under 47KΩ	51K~ 100KΩ	110K~ 330KΩ	Over 360KΩ	
	1/4W & Over	Under 100KΩ	110K~ 1MΩ	1.1M~ 2.2MΩ	Over 2.4MΩ	
短時間過負荷 Short time overload	±(1%+0.05Ω)以內。 不得有機械的損傷。 within ±(1%+0.05Ω) No evidence of mechanical damage.					5.5 項參照 Comply with 5.5 額定電壓 X 2.5 倍, 5 秒。 不可超過最高過負荷電壓(見表-1) Rated voltage X 2.5 times, 5s But not to exceed maximum overload voltage. (See table-1)
絕緣抵抗 Insulation resistance	10 <sup>4</sup> MΩ 以上。 10 <sup>4</sup> MΩ or more					5.6 項參照 Comply with 5.6 置於 V 型槽方法。 施加直流電壓 500V 60 秒。 V-block method Resistor shall be tested at DC 500V for 60 seconds.
耐電壓 Dielectric withstanding voltage	無電弧放電、燒損及絕緣破壞等異狀。 No evidence of flashover mechanical damage, arcing or insulation breakdown.					5.7 項參照 Comply with 5.7 常壓, 置於 V 型槽方法。 施加個別規定之交流電壓 60 秒。(見表-1) Constant pressure, V-block method Resistor shall be tested at AC potential respectively for 60 seconds.(See table-1)
斷續過負荷 Pulse overload	±(0.75%+0.05Ω)以內。 within ±(0.75%+0.05Ω)					5.8 項參照 Comply with 5.8 額定電壓 X 4 倍, 10000 回(1 秒 ON, 25 秒 OFF)。 不可超過最高斷續電壓(見表-1) Rated voltage X 4 times, 10000 cyc.(1s ON, 25s OFF) But not to exceed maximum pulse voltage.(See table-1)
端子強度 Terminal strength	端子不得斷裂及鬆弛。 No evidence of mechanical damage.					6.1 項參照 Comply with 6.1 引張強度: 25N(2.5Kgf), 保持 10 秒。 Tensile strength: 25N(2.5kgf), for 10 seconds. 扭轉強度: 360° 交互迴轉 5 回。 Torsional strength: Rotated through 360°, 5 rotations.




**FIXED CARBON FILM RESISTORS**  
**碳素皮膜固定電阻器**

項目 Item	規格值 Performance	試驗方法 (依據 JIS C 5202) Test methods (Conform to JIS C 5202)
焊錫耐熱性 Resistance to soldering heat	±(0.5%+0.05Ω)以內。 不得有機械的損傷。 within ±(0.5%+0.05Ω) No evidence of mechanical damage.	6.4 項參照 Comply with 6.4 350±10°C, 3±0.5 秒 或 260±5°C, 10±1 秒, 試驗後放置 3 小時。 350±10°C, 3±0.5s or 260±5°C, 10±1s, After test leave for 3h.
焊錫附着性 Solderability	導線至少 95%以上新錫覆蓋。 Covered with new solder by 95% at least.	6.5 項參照 Comply with 6.5 焊錫溫度：245±5°C。 浸錫時間：5±0.5 秒。 Test temperature of solder: 245±5°C Dipping time in solder: 5±0.5s
耐溶劑性 Resistance to solvent	塗裝及色碼不得脫落。 No deterioration of protective coating and markings.	6.9 項參照 Comply with 6.9 放入異丙醇溶劑之超音波機內，保持 3 分鐘。 Specimens shall be immersed in a bath of isopropyl alcohol completely for 3 minutes with ultrasonic.
溫度循環 Temperature cycle	±(1%+0.05Ω)以內。 不得有機械的損傷。 within ±(1%+0.05Ω) No evidence of mechanical damage.	7.4 項參照 Comply with 7.4 低溫側：-55±3°C：30 分鐘，室溫：2~3 分鐘 高溫側：+155±2°C：30 分鐘，室溫：2~3 分鐘 5 回 Low side：-55±3°C：30min, Room temp.：2 to 3min High side：+155±2°C：30min, Room temp.：2 to 3min 5 cycles
耐濕負荷壽命 Load life in humidity	< 100KΩ：±3% ≥ 100KΩ：±5%	7.9 項參照 Comply with 7.9 40±2°C，濕度 90~95%，1000 小時 定格電壓(90 分鐘 ON, 30 分鐘 OFF) 40±2°C, 90 to 95%RH, 1000h Rated voltage (90 min ON, 30 min OFF)
負荷壽命 Load life	< 100KΩ：±(2%+0.05Ω) ≥ 100KΩ：±3%	7.10 項參照 Comply with 7.10 70±3°C，1000 小時 定格電壓(90 分鐘 ON, 30 分鐘 OFF) 70±3°C, 1000h Rated voltage (90 min ON, 30 min OFF)






4. 表示 Indication  
色碼 Color Code



顏色 Color	第1數字 1st figure	第2數字 2nd figure	第3數字 3rd figure	倍 率 Multiplier	誤 差 率 Tolerance
黑 Black	0	0	0	$10^0$	
棕 Brown	1	1	1	$10^1$	±1% (F)
紅 Red	2	2	2	$10^2$	±2% (G)
橙 Orange	3	3	3	$10^3$	
黃 Yellow	4	4	4	$10^4$	
綠 Green	5	5	5	$10^5$	±0.5% (D)
藍 Blue	6	6	6	$10^6$	±0.25%(C)
紫 Violet	7	7	7	$10^7$	±0.1% (B)
灰 Gray	8	8	8		±0.05%(A)
白 White	9	9	9		
金 Gold				$10^{-1}$	±5% (J)
銀 Silver				$10^{-2}$	±10% (K)
無 Plain					±20% (M)






5. 外形寸法 External dimensions

5.1 散裝 B 形與 臥式 PU 形系列 B type (Straight) & PU-Form series (Horizontal Forming)

B Type

PU Type




單位：mm  
 Unit：mm

種類 Type		尺寸 Dimensions					
普通型 Normal Size	小型化 Small Size	L	$\phi D$	$\phi d$	H	P	h
CF1/8W	CF1/4WS	3.2±0.2	1.8±0.2	0.40±0.05	28.0±3.0	5.0±1.0	3.5±0.5
CF1/4W	CF1/2WS	6.5±0.5	2.3±0.3	0.50±0.05	28.0±3.0	10.0±1.0	3.5±0.5
CF1/2W	CF1WS	9.0±1.0	3.2±0.5	0.60±0.10	28.0±3.0	12.5±1.0	3.5±0.5
CF1W	CF2WS	12.0±1.0	4.5±0.5	0.65±0.10	32.0±3.0	15.0±1.0	3.5±0.5
CF2W	CF3WS	15.5±1.0	5.0±1.0	0.70±0.10	35.0±3.0	20.0±1.0	3.5±0.5
CF3W		17.5±1.0	6.5±1.0	0.70±0.10	35.0±3.0	25.0±1.0	3.5±0.5




PUK Type (Kinked Forming)



單位：mm  
Unit：mm

種類 Type		尺寸 Dimensions						
普通型 Normal Size	小型化 Small Size	L	$\phi D$	$\phi d$	P	$h_1$	$h_2$	K
CF1/4W	CF1/2WS	6.5±0.5	2.3±0.3	0.50±0.05	10±0.5	5.0±1.0	3.5±0.5	2.0±0.5
CF1W	CF2WS	12.0±1.0	4.5±0.5	0.65±0.10	15.0±1.0	5.0±1.0	2.7-3.6	2.0±0.5
CF2W	CF3WS	15.5±1.0	5.0±1.0	0.70±0.10	22.0±1.0	5.0±1.0	2.7-3.6	2.0±0.5

PUG Type (Free-standing Forming)




單位：mm  
Unit：mm

種類 Type		尺寸 Dimensions						
普通型 Normal Size	小型化 Small Size	L	$\phi D$	$\phi d$	P	$h_1$	$h_2$	t
CF1/2W	CF1WS	9.0±1.0	3.2±0.5	0.70±0.10	12.5±1.0	6.0±2.0	4.5±0.5	1.4±0.2
CF1W	CF2WS	12.0±1.0	4.5±0.5	0.70±0.10	15.0±1.0	6.0±2.0	4.5±0.5	1.4±0.2
CF2W	CF3WS	15.5±1.0	5.0±1.0	0.70±0.10	20.0±1.0	10.0±2.0	4.5±0.5	1.4±0.2
CF3W	CF5WS	17.5±1.0	6.5±1.0	0.70±0.10	25.0±1.0	10.0±2.0	4.5±0.5	1.4±0.2
CF5W		24.5±1.0	9.0±1.0	0.70±0.10	30.0±1.0	12.0±2.0	4.5±0.5	1.4±0.2




5.2 立式 PF 形系列 PF-Form series (Vertical Forming)


PF Type




Double Kinked Forming PFKK Type



Single Kinked Forming PFK1 Type



Single Kinked Forming PFK2 Type



單位：mm


Unit：mm

種類 Type		尺寸 Dimensions								
普通型 Normal Size	小型化 Small Size	L	$\phi D$	$\phi d$	P	h	$h_1$	H	E	K
CF1/4W	CF1/2WS	6.5±0.5	2.3±0.3	0.50±0.05	5-7	3.5±0.5	5.0±2.0	18 Max.	2.5±1.0	2.0±0.5
CF1/2W	CF1WS	9.0±1.0	3.2±0.5	0.60±0.10	5-7	3.5±0.5	5.0±2.0	21 Max.	2.5±1.0	2.0±0.5
CF1W	CF2WS	12.0±1.0	4.5±0.5	0.65±0.10	5-9	3.5±0.5	5.0±2.0	24 Max.	2.5±1.0	2.0±0.5
CF2W	CF3WS	15.5±1.0	5.0±1.0	0.70±0.10	5-9	3.5±0.5	5.0±2.0	28 Max.	2.5±1.0	2.0±0.5
CF3W		17.5±1.0	6.5±1.0	0.70±0.10	5-9	3.5±0.5	5.0±2.0	30 Max.	2.5±1.0	2.0±0.5

Remarks: c= 1.0 max. , c+h=3.7±0.5



5.3 帶裝 Axial Lead Taping  
Txx Type



單位：mm  
Unit：mm

種類 Type		帶狀 Taping	尺寸 Dimensions									
普通型 Normal Size	小型化 Small Size		L	W	P	L1-L2 Max.	T	Z Max.	R Max.	t Max.	e Max.	S Max.
CF1/8W	CF1/4WS	T26	3.2±0.2	26 <sup>+1.0</sup> <sub>-0</sub>	5±0.3	0.5	6±0.5	0.8	0	2.5	0.1	0.5
		*T52	3.2±0.2	52 <sup>+1.5</sup> <sub>-0</sub>	5±0.3	1.0	6±0.5	0.8	0	2.5	0.5	0.5
CF1/4W	CF1/2WS	T26	6.5±0.5	26 <sup>+1.0</sup> <sub>-0</sub>	5±0.3	1.0	6±0.5	0.8	0	2.5	0.1	0.5
		*T52	6.5±0.5	52 <sup>+1.5</sup> <sub>-0</sub>	5±0.3	1.0	6±0.5	0.8	0	2.5	0.5	0.5
CF1/2W	CF1WS	T52	9.0±1.0	52 <sup>+1.5</sup> <sub>-0</sub>	5±0.3	1.0	6±0.5	0.8	0	2.5	0.5	0.5
CF1W	CF2WS	T52	12.0±1.0	52 <sup>+1.5</sup> <sub>-0</sub>	5±0.5	1.0	6±0.5	0.8	0	2.5	0.5	0.5
		T63	12.0±1.0	63±1.5	5±0.5	1.0	6±0.5	1.2	1.0	2.5	0.5	0.8
		*T73	12.0±1.0	73±1.5	5±0.5	1.0	6±0.5	1.2	1.0	2.5	0.5	0.8
CF2W	CF3WS	T63	15.5±1.0	63±1.5	10±0.5	1.0	6±0.5	1.2	1.0	2.5	0.5	0.8
		*T73	15.5±1.0	73±1.5	10±0.5	1.0	6±0.5	1.2	1.0	2.5	0.5	0.8
CF3W		T83	15.5±1.0	83±1.5	10±0.5	1.0	6±0.5	1.2	1.0	2.5	0.5	0.8
		T73	17.5±1.0	73±1.5	10±0.5	1.0	6±0.5	1.2	1.0	2.5	0.5	0.8

Remarks: Marked "\*" means standard taping dimensions, standard for 3W is bulk packing (B Type).



6. 包裝 Package


6.1 散裝品包裝 Bulk in box packing

6.1.1 表示項目 Indication

- (1) 客戶品號 Customer Part No.
- (2) 製造品號 Manufacturer Part No.
- (3) 製造批號 Lot No.
- (4) 數量 Quantity
- (5) 製造者名 Manufacturer

6.1.2 包裝盒尺寸和數量

Packing box size and quantity



種類 Type		形狀 Form	塑膠袋包裝數 Polyethylene bag (pcs)	紙盒包裝數 Paper box (pcs)	尺寸 Dimensions (mm)		
普通型 Normal Size	小型化 Small Size				L	W	H
CF1/8W	CF1/4WS	B, PU & PF-Form series	1000	10000	238	140	70
CF1/4W	CF1/2WS	B, PU & PF-Form series	1000	10000			
CF1/2W	CF1WS	B	250	5000			
		PU & PF-Form series	500	5000			
CF1W	CF2WS	B	200	2000			
		PU & PF-Form series	500	3000			
CF2W	CF3WS	B	200	1000			
		PU & PF-Form series	500	2000			
CF3W		B	100	500			
		PU & PF-Form series	250	1000			




6.2 帶裝品包裝 Tape in box packing (Ammo packing)

6.2.1 表示項目 Indication

- (1) 客戶品號 Customer Part No.
- (2) 製造品號 Manufacturer Part No.
- (3) 製造批號 Lot No.
- (4) 數量 Quantity
- (5) 製造者名 Manufacturer

6.2.2 包裝盒尺寸和數量

Packing box size and quantity



種類 Type		形狀 Form	包裝數量 Quantity (pcs)	尺寸 Dimensions (mm)		
普通型 Normal Size	小型化 Small Size			L	W	H
CF1/8W	CF1/4WS	T26	5000	258	50	63
		T52	5000	258	72	63
CF1/4W	CF1/2WS	T26	5000	258	50	100
		T52	5000	258	72	98
CF1/2W	CF1WS	T52	1000	258	72	43
CF1W	CF2WS	T52	1000	258	72	75
		T63	1000	258	88	76
		T73	1000	258	96	72
CF2W	CF3WS	T73	1000	258	90	92
		T83	1000	258	105	92
CF3W		T73	1000	258	90	92
		T83	1000	258	105	92